

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 September 2005 (01.09.2005)

PCT

(10) International Publication Number  
**WO 2005/080847 A1**

(51) International Patent Classification<sup>7</sup>: **F16L 5/02, 5/10**

Dennis [GB/GB]; c/o Durapipe UK, Walsall Road, Norton Canes, Staffordshire WS11 9NS (GB).

(21) International Application Number:

PCT/GB2005/000554

(74) Agents: **TOWNSEND, Victoria, Jayne et al.**; Fry Heath & Spence LLP, The Gables, Massetts Road, Horley, Surrey RH6 7DQ (GB).

(22) International Filing Date: 16 February 2005 (16.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0403471.6 17 February 2004 (17.02.2004) GB

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **GLYN-WED PIPE SYSTEMS LTD** [GB/GB]; 1 Suffolk Way, Sevenoaks, Kent TN13 1SD (GB).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STATHAM, Richard** [GB/GB]; c/o Durapipe Ltd, Walsall Road, Norton Canes, Staffordshire WS11 9NS (GB). **O'DEA,**

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH,

[Continued on next page]

(54) Title: SEALING OF PIPE TO SUMP INTERFACES



(57) Abstract: A coupling assembly for sealing an interface between a pipe and a sump wall, the assembly comprising; a sleeve (21) configured to be inserted in an aperture in a sump wall (20) and having a bore suitable for receiving a collar (22), the sleeve (21) having in diametrical cross section along its inner surface one or more circumferentially arranged, longitudinally extending undulations (21a); a collar (22) configured to be received between the sleeve (21) and the pipe P, being fusible to the pipe P and having a stepped internal diameter (22a) for receiving a swaging bung (23), a swaging bung (23) configured to be received in the stepped portion (22a) of the internal diameter of the collar (22) and configured to receive a pipe P; at least one washer (24a, 24b) having a diameter sized to fit the outside diameter of the sleeve (21); and a quantity of matting (25) comprising a material which is leak tight bondable to the material of the sump wall (20).



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.